



# Warm Mix Asphalt Perpetual Pavement

The Ohio Asphalt Paving Conference  
February 7, 2007

J. Ludwig Figueroa, Ph.D., P.E., Professor  
Department of Civil Engineering Ohio Univ.  
Ohio Research Institute for Transportation and the  
Environment (ORITE)

In cooperation with  
Prof. Shad M. Sargand and Sang-Soo Kim



# Warm Mix Asphalt (WMA) Background

- **Warm Mix Asphalt (WMA) was first Introduced in Europe in 1995**
- **Advantages:**
  - **reduced energy consumption in mix preparation,**
  - **reduced emissions and consequently reduced fumes and undesirable odors,**
  - **reduced binder aging,**
  - **extended construction seasons in temperate climates.**
- **WMA requires additives, which add to the cost, however the additional expenditure is offset by energy savings and reduced emissions**

# Four kinds of WMA

- **Aspha-min**
  - Addition of sodium aluminum silicate or zeolite in a machine.
- **Evotherm**
  - Includes additives in the form of an emulsion to improve the coating and workability of WMA mixes.
- **Sasobit**
  - Uses foam in the form of a paraffin-wax compound extracted from coal gasification.
- **WAM-Foam**
  - Uses a soft binder and a hard foamed binder added at different times during the mixing process.
- **In ORITE research, only the first three are being investigated**
  - WAM-Foam dropped from project in consultation with Ohio Department of Transportation (ODOT) engineers and Flexible Pavements of Ohio

# Aspha-Min mixing at asphalt plant



# Previous Research in the USA

- **Field demonstration projects in Florida, North Carolina, and Tennessee**
- **National Center for Asphalt Technology (NCAT) at Auburn University reports on Aspha-min (Report 05-04) and Sasobit (Report 05-06)**
  - **Improved compaction at temperatures as low as 190°F (88°C)**
  - **No effect on resilient modulus or rutting potential**
  - **Potential for increased susceptibility for moisture damage**
    - **For Aspha-min this can be reduced by adding hydrated lime**

# ORITE research project

- Detailed field, controlled environment, and laboratory evaluation of Aspha-min, Evotherm, and Sasobit and Conventional mixes
  - Field study in Guernsey County, OH on State Route 541
  - Controlled load and environment test at ORITE's Accelerated Pavement Load Facility (APLF) in Lancaster, OH
  - Laboratory studies of cores, field-procured beams and prepared specimens
- Project sponsored by the Ohio Department of Transportation (ODOT) and the the US Federal Highway Administration (FHWA)

# GUE-541 Field Study

- **Four test sections on asphalt overlay of State Route 541 in Guernsey County between Kimbolton and Plainfield, West of I-77**
  - **Site selected by ODOT**
  - **Overlay constructed first half of September 2006**
  - **Contractor: Shelley and Sands, Inc.**
- **Overlay layers**
  - **Top: 1.25 in (3.18 cm) of selected mix**
    - **Aspha-min, Sasobit, Evotherm, or conventional Hot Mix Asphalt (HMA)**
  - **Bottom: 0.75 in (1.90 cm) HMA**
- **Section lengths: 2.70 miles (4.34 km) to 3.07 miles (4.94 km)**

# **GUE-541 Forensic Assessment of Existing Pavement Structure**

- **Falling Weight Deflectometer (FWD)**
  - **Back calculate pavement layer stiffness**
- **Surface Profile**
- **Dynamic Cone Penetrometer (DCP)**
- **Forensic analysis used to identify weak spots needing remediation prior to overlay**



# GUE-541 Construction Monitoring


- **FWD after overlay prior to traffic and at subsequent time intervals**
- **Periodic visual surveys of pavement surface condition**
- **Infrared camera used to measure temperature during construction**
  - **Temperature variations may be compared to possible variations in asphalt density**
- **Profilometer measurements**
- **Forensic analysis following Strategic Highway Research Program (SHRP) protocol of any sections showing distress during three-year research period**

# Infrared Camera

Images from APLF



Evotherm



Conventional HMA

Note with software program cursor can be moved and temperature read off upper right corner.

Temperatures in Fahrenheit ( $216^{\circ}\text{F}=102^{\circ}\text{C}$ ,  $301^{\circ}\text{F}=149^{\circ}\text{C}$ )

# Energy, Emissions, and Cost Assessment

- Stack and Emissions tests by Mar-Zane Materials Quality Control Laboratory of Shelly and Sands
- Exposure/emissions sampling during construction by EES Group
  - Environmental sensors placed on paver and along side of road
- Construction costs for each section were also noted

# Emissions sampling on paver






# Roadside emissions sampling




# Infrared Camera

Images from GUE 541



Sasobit WMA



Sasobit WMA

Temperatures in Fahrenheit ( $216^{\circ}\text{F}=102^{\circ}\text{C}$ ,  $301^{\circ}\text{F}=149^{\circ}\text{C}$ )

# Controlled Load and Environment Testing at the APLF

- **WMA and HMA surface layers have been built and will be tested at the Accelerated Pavement Load Facility (APLF)**
  - **Same types as those used on GUE-541 (Aspha-min, Evotherm, Sasobit, and HMA)**
  - **Built on perpetual pavement sections at two thicknesses**
- **Planned Testing under load at three temperatures:**
  - high (100°F (38°C)),**
  - medium (70°F (21°C)),**
  - and low (40°F (0°C))**
- **FWD**
- **Collect Pavement Response data**
- **Infrared camera (during construction)**

# Accelerated Pavement Load Facility (APLF)


- Complete, full-scale two-lane pavement, base, and subgrade construction.
  - Testing of Asphaltic Materials and PCC.
  - Full environmental control to regulate humidity and temperature from 10°F (-12°C) to 130°F (54°C).
  - Multiple test paths across the 32-ft (9.75 m) wide pavement.
- 
- The image shows the interior of the Accelerated Pavement Load Facility (APLF). It is a long, narrow industrial building with a high ceiling and bright lighting. The floor is a dark, smooth surface, likely asphalt or concrete, with a central lane. A large, green and yellow vehicle, possibly a truck or a specialized testing rig, is positioned in the center of the lane. The walls are white, and there are various pipes and equipment visible. The overall appearance is that of a well-maintained, modern testing facility.
- A rolling tire load of 9000 lb (40 kN) to 30,000 lb (133 kN) can be applied to simulate a passing truck with standard single or dual tires or wide single tires, up to 500 times per hour




# APLF Monitoring

- **Environmental parameters**
  - **pavement layer temperature**
  - **Base temperature and moisture**
  - **Subgrade temperature, moisture, and groundwater table**
- **Load parameters**
  - **Displacement**
  - **Strain**
  - **Pressure**
- **Also seasonal response in terms of displacement and pressure**


# Pavements constructed in APLF

Surface	Direction of wheel 		Lane width
Evotherm WMA	1.25" (3.18 cm) Evotherm WMA	1.25" (3.18 cm) Evotherm WMA	8 ft (2.44 m)
	3" (7.62 cm) ODOT 448 Type II AC	3" (7.62 cm) ODOT 448 Type II AC	
	4.75" (12.1 cm) ODOT 448 Type I AC	7.75" (19.7 cm) ODOT 448 Type I AC	
	4" (10.2 cm) Fatigue Resistant Layer	4" (10.2 cm) Fatigue Resistant Layer	
	9" (22.9 cm) ODOT 304 DGAB	6" (15.3 cm) ODOT 304 DGAB	
	48" (120 cm) A6-A7 Subgrade	48" (120 cm) A6-A7 Subgrade	
Sasobit WMA	1.25" (3.18 cm) Sasobit WMA	1.25" (3.18 cm) Sasobit WMA	8 ft (2.44 m)
	3" (7.62 cm) ODOT 448 Type II AC	3" (7.62 cm) ODOT 448 Type II AC	
	5.75" (14.6 cm) ODOT 448 Type I AC	7.75" (19.7 cm) ODOT 448 Type I AC	
	4" (10.2 cm) Fatigue Resistant Layer	4" (10.2 cm) Fatigue Resistant Layer	
	8" (20.3 cm) ODOT 304 DGAB	6" (15.3 cm) ODOT 304 DGAB	
	48" (120 cm) A6-A7 Subgrade	48" (120 cm) A6-A7 Subgrade	
Aspha-min WMA	1.25" (3.18 cm) Aspha-min WMA	1.25" (3.18 cm) Aspha-min WMA	8 ft (2.44 m)
	3" (7.62 cm) ODOT 448 Type II AC	3" (7.62 cm) ODOT 448 Type II AC	
	6.75" (17.1 cm) ODOT 448 Type I AC	7.75" (19.7 cm) ODOT 448 Type I AC	
	4" (10.2 cm) Fatigue Resistant Layer	4" (10.2 cm) Fatigue Resistant Layer	
	7" (17.8 cm) ODOT 304 DGAB	6" (15.3 cm) ODOT 304 DGAB	
	48" (120 cm) A6-A7 Subgrade	48" (120 cm) A6-A7 Subgrade	
Conventional HMA	1.25" (3.18 cm) Conventional HMA	1.25" (3.18 cm) Conventional HMA	8 ft (2.44 m)
	3" (7.62 cm) ODOT 448 Type II AC	3" (7.62 cm) ODOT 448 Type II AC	
	7.75" (19.7 cm) ODOT 448 Type I AC	7.75" (19.7 cm) ODOT 448 Type I AC	
	4" (10.2 cm) Fatigue Resistant Layer	4" (10.2 cm) Fatigue Resistant Layer	
	6" (15.3 cm) ODOT 304 DGAB	6" (15.3 cm) ODOT 304 DGAB	
	48" (120 cm) A6-A7 Subgrade	48" (120 cm) A6-A7 Subgrade	
← 22.5 ft (6.9 m)		← 22.5 ft (6.9 m) →	

# Instrumentation in APLF








PLAN VIEW



PROFILE VIEW

(Not to Scale)

-  Single Layer Deflectometer
-  Longitudinal Gage
-  Transverse Gage
-  Pressure Cell
-  T Type Thermocouples


# Laboratory Tests

- Based on samples of mixes and additives taken at the APLF and at GUE-541
- Samples taken at the time of construction
- Additional core samples taken or to be taken at GUE-541 after construction
  - Three months, one year, two years
- Testing by both ORITE and NCAT

# ORITE Laboratory Tests

- Density Tests at time of construction, and after three months, one year, and two years.
- Bond strength between layers
- Assessment of reduced aging during construction.
- Indirect tensile strength determined at 77 °F (25°C), after three months, one year, and two years.
- Assessment of in-place densification under traffic, and relation to air voids at time of construction.
- Aging of binder as a function of time.
- Beam fatigue tests (AASHTO T321).
- Fracture energy – an alternative method of assessing resistance to cracking.
- Other methods of assessing cracking potential may also be used, such as the TTI overlay tester.
- Low-temperature cracking (IDT test (AASHTO T322))

# Indirect Tensile Strength (0 & 3 month cores)



# NCAT Laboratory Tests

- Moisture content in truck at time of application,
- Gyratory compaction,
- Volumetric properties,
- Hamburg Tests for moisture susceptibility and rutting,
- Rutting potential,
- Maximum specific gravity,
- Tensile strength ratio test,
- Anticipated in-place field density
- Thermal stress restricted specimen test may be conducted as an option

# RUSS COLLEGE of Engineering and Technology



<http://webce.ent.ohiou.edu/orite/>

[www.ohio.edu/engineering](http://www.ohio.edu/engineering)



**OHIO**  
UNIVERSITY